

## TECHNICAL DATA SHEET

**EcoPrint® 5109**

Edition No. 01 - 13/01/2020

### PRODUCT DESCRIPTION

**EcoPrint® 5109** is a standard sheetfed varnish.

### CHARACTERISTICS

Based in phenol free resin and vegetable oils.

Solid content: +/- 95%.

Good lithographic properties.

### PRODUCT SPECIFICATIONS<sup>1</sup>

	Product Specification	Typical Properties	Units
Viscosity (Rheometer, 23°C, 25 s <sup>-1</sup> )	200 - 280	240	Pa.s
<b>Cloud Point (10% in T.O. 6/9 AF New)</b>	<b>80 - 140</b>	<b>100</b>	<b>°C</b>
Tack (Lithotack, 0.4 gr, 32.2°C, 400rpm, 60'')	100 - 150	120	-----

### APPLICATIONS

Ready-to-use varnish for offset inks.

### FORM OF SUPPLY

Open lid drums (190 kg);

Road tanks.

### SHELF LIFE

Up to six months under normal storage conditions.

<sup>1</sup>Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.