

TECHNICAL DATA SHEET

EcoResin® 5402

Edition No. 01 - 13/01/2020

PRODUCT DESCRIPTION

EcoResin® 5402 is a maleic modified glycerol ester of gum rosin.

CHARACTERISTICS

Yellow solid.

Good nitrocellulose compatibility.

Solubility in esters and ketones, like MEK.

Total solubility in aromatic hydrocarbon solvent diluents, like toluene or xylene.

PRODUCT SPECIFICATIONS¹

	Product Specification	Typical Properties	Units
Acid Number	35 max	30	mg KOH/g
Softening Point (R&B)	135-140	137	-----
Color Gardner (50%, Toluene)	9 max	6/7	°C
Viscosity @ 25°C (DIN Cup n°4, 50% Toluene)	15 - 35	25	s

APPLICATIONS

Resin specially recommended for:

- Nitrocellulose primers and varnishes;
- Cellulose enamels.

FORM OF SUPPLY

Flakes in 25 kg bags on pallet 1000 kg weight;
in 500, 1000 kg big-bag.

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.