

TECHNICAL DATA SHEET

EcoTack® 3309

Edition No. 01 - 13/01/2020

PRODUCT DESCRIPTION

EcoTack® 3309 is a triethylene glycol ester of gum rosin.

CHARACTERISTICS

Light yellow viscous liquid with:

- Excellent tack;
- Good compatibility with natural and synthetic rubber;
- Good compatibility with EVA polymers;
- Good compatibility with wax;
- Total compatibility with aliphatic hydrocarbon resins;
- Very Low VOC's.

PRODUCT SPECIFICATIONS¹

	Product Specification	Typical Properties	Units
Acid Number	20 max	18	mg KOH/g
Color Gardner (50%, Toluene)	6 max	5	-----
Viscosity (Rheometer @20°C)	85000 - 115000	100000	mPa.s

APPLICATIONS

Is recommended for use as tackifier in:

- Floor coating adhesives;
- P.S.A.;
- Permanent tack hot melt adhesives.

FORM OF SUPPLY

Metallic Drums (200 kg).

IBC's (1000 kg).

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.