

TECHNICAL DATA SHEET

EcoTack® 5210

Edition No. 01 - 13/01/2020

PRODUCT DESCRIPTION

EcoTack® 5210 is a fumaric modified glycerol ester of gum rosin.

CHARACTERISTICS

Light yellow solid.

High oxidative stability.

Excellent adhesion with glass beads, anti-skid aggregates and the pavement.

Stable in viscosity.

PRODUCT SPECIFICATIONS¹

	Product Specification	Typical Properties	Units
Acid Number	15 max	10	mg KOH/g
Softening Point (R&B)	98 - 102	100	°C
Color Gardner (50%, Toluene)	4 max	2/3	-----

APPLICATIONS

Resin specially manufactured for high quality thermoplastic traffic line compounds.

FORM OF SUPPLY

Flakes in 25 kg bags on pallet 1000 kg weight;
in 500, 1000 kg big-bag.

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.