

## TECHNICAL DATA SHEET

**EcoTack® 5211**

Edition No. 01 - 13/01/2020

### PRODUCT DESCRIPTION

**EcoTack® 5211** is a fumaric modified glycerol ester of gum rosin.

### CHARACTERISTICS

Yellow solid.

High oxidative stability.

Excellent adhesion with glass beads, anti-skid aggregates and the pavement.

Good oil & gas resistance.

Stable in viscosity.

### PRODUCT SPECIFICATIONS<sup>1</sup>

	Product Specification	Typical Properties	Units
Acid Number	10 - 20	15	mg KOH/g
Softening Point (R&B)	100 - 110	105	°C
Color Gardner (50%, Toluene)	5 max	3/4	-----

### APPLICATIONS

Resin specially manufactured for high quality thermoplastic traffic line compounds.

### FORM OF SUPPLY

**Flakes** in 25 kg bags on pallet 1000 kg weight;  
in 500, 1000 kg big-bag.

### SHELF LIFE

Up to six months under normal storage conditions.

<sup>1</sup>Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.