

TECHNICAL DATA SHEET

EcoPrint® 5106

Edition No. 01 - 13/01/2020

PRODUCT DESCRIPTION

EcoPrint® 5106 is a standard grinding/free flow varnish.

CHARACTERISTICS

Based in modified phenolic resins, vegetable oil and mineral oil.

Solid content: +/- 65%.

Good pigment wetting.

Good lithographic properties.

High gloss.

PRODUCT SPECIFICATIONS¹

	Product Specification	Typical Properties	Units
Viscosity (Rheometer, 23°C, 25 s ⁻¹)	25 – 55	40	Pa.s
Cloud Point (10% in T.O. 6/9 AF New)	60 – 110	80	°C
Tack (Lithotack, 0.4 gr, 32.2°C, 400rpm, 60'')	50 – 90	70	-----

APPLICATIONS

Ready-to-use varnish for grinding sheetfed offset inks.

FORM OF SUPPLY

Open lid drums (190 kg);

Road tanks.

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.