

TECHNICAL DATA SHEET

EcoPrint® 5107

Edition No. 01 - 13/01/2020

PRODUCT DESCRIPTION

EcoPrint® 5107 is a standard letdown/gel varnish.

CHARACTERISTICS

Based in modified phenolic resins, vegetable oil and mineral oil.

Solid content: +/- 55%.

Good press stability.

Good lithographic properties.

High gloss.

PRODUCT SPECIFICATIONS¹

	Product Specification	Typical Properties	Units
Viscosity (Rheometer, 23°C, 25 s ⁻¹)	250 – 300	275	Pa.s
Cloud Point (10% in T.O. 6/9 AF New)	120 – 150	140	°C
Tack (Lithotack, 0.4 gr, 32.2°C, 400rpm, 60'')	80 – 120	100	-----

APPLICATIONS

Ready-to-use varnish for letdown sheetfed offset inks.

FORM OF SUPPLY

Open lid drums (190 kg);

Road tanks.

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.