

TECHNICAL DATA SHEET

EcoTack® 1302

Edition No. 01 - 13/01/2020

PRODUCT DESCRIPTION

EcoTack® 1302 is a polymerized gum rosin.

Polymerization is a chemical reaction in which a part of the abietic acid present in the gum rosin is converted to a dimer, by linking two molecules of it. This reaction leads to the polymerized gum rosin.

CHARACTERISTICS

Dark yellow solid.

This rosin is:

- Soluble in aromatic and aliphatic solvents;
- Totally compatible with natural and synthetic polymers;
- Resistant to oxidation.

PRODUCT SPECIFICATIONS¹

	Product Specification	Typical Properties	Units
Acid Number	140 max	120	mg KOH/g
Softening Point (R&B)	84 - 88	86	°C
Color Gardner (50%, Toluene)	6 max	4/5	-----
Abietic Acid	10 max	5/6	%

APPLICATIONS

Has application in:

- Floor coating adhesives;
- Adhesives;
- Lithographic Inks;
- Pigments.

FORM OF SUPPLY

Flakes in 25 kg paper or polypropylene bags on pallet 500 or 1000 kg weight.

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.