

TECHNICAL DATA SHEET

EcoTack® 5202

Edition No. 01 - 13/01/2020

PRODUCT DESCRIPTION

EcoTack® 5202 is a modified pentaerythritol ester of gum rosin.

CHARACTERISTICS

Yellow solid.

This rosin has:

- excellent internal cohesion;
- good compatibility with wax;
- good compatibility with EVA polymers;
- total compatibility with aliphatic hydrocarbons.

PRODUCT SPECIFICATIONS¹

	Product Specification	Typical Properties	Units
Acid Number	20 max	15	mg KOH/g
Softening Point (R&B)	123 - 129	125	°C
Color Gardner (50%, Toluene)	9 max	6/7	-----

APPLICATIONS

Resin specially manufactured to be used as tackifier in hot-melt adhesives where a good mechanical resistance is necessary.

FORM OF SUPPLY

Flakes in 25 kg bags on pallet 1000 kg weight;
in 500, 1000 kg big-bag.

SHELF LIFE

Up to six months under normal storage conditions.

¹Analytical Methods are available on request.

The information in this Technical Data Sheet is, to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information. It is the customers' responsibility to assess and to test our products in order to satisfy themselves as to the suitability of the products to their particular purpose. We are, at all times, willing to study customer's specific outcomes involving our products in order to enable their most effective use.